




The RAS challenges of NFV




Huawei Overview



Driving the Industry Forward Through Innovation

- 2004: Distributed Base Transceiver Station
- 2005: SingleFAN (DSL/Fiber/Cable)
- 2006 : All IP Network
- 2007: Single Radio Access Network
- 2008: Cloud Computing
- 2009: Optical Transport Network Standard
- 2010 : Single Strategy
- 2011: 400G DWDM
- **2012: SoftCOM**
- 2013: 5G 、 Agile Network

In the last 20 years, the communication industry has undergone 3 profound changes.....




**What's
Next?**


- 1. From Analog to Digital**
- 2. From Fixed to mobile communication.**
- 3. From TDM to IP/Internet**

The New Change—— Introduce Internet changes to Telecom.....

Cloud Computing, Big Data, OpenFlow, NFV (Network Functions Virtualization), SDN(Software Defined Networks),.....



NFV now is the mainstream in Telecom



Members from CT and IT are working together:

■ Carriers:


AT&T、Verizon、BT、FT、DT、Vodafone、Telefonica、TI、Century Link

■ CT Vendors:

Huawei、Ericsson、Alcatel-Lucent、NSN、NEC.....


■ IT Vendors:

HP、intel、IBM、CISCO、Juniper.....



Huawei is Working together with Industry to enable NFV

- Reliability & Availability working group is one of the four NFV working group for its importance.
- Huawei actively engaged in and make key contributions.



ETSI NFV RELAV WG Specification outline:


Contents ⁺	
1.	Scope.....7
2.	References.....7
3.	Definitions, symbols and abbreviations.....7
4.	Resiliency Problem Description & Objectives.....9
5.	Resilience Principles in NFV Environments:.....13
6.	Usecase Analysis & High-Level Service Requirements.....17
7.	Reliability & Availability Architecture Framework.....23
8.	Service Availability.....27
9.	Failure Prevention.....36
10.	Failure Detection.....43
11.	Resiliency Flows.....50
12.	Deployment and engineering guidelines.....60
13.	Gaps in Industry.....68
14.	Recommendations.....70

NFV Challenges for example.....Far more about Function

5. Some HA mechanisms might need to be re-architected because of the virtualization.

RAS challenges caused by

- ✓ **New architecture:** Decoupled HW&SW, COTS, more layers,.....
- ✓ **New Characteristics:** Scalable, Dynamic/Elastic ,.....
- ✓ **New system:** Normally more SW bugs for a completed new system



2. New fault modes for the new virtualization layer.

1. The virtualization has separated HA and the HW fault detection system.

4. Cloud NaaS' fast failure detection and recovery for the links, switches and hosts in the huge and complex network.

3. No common interface or no standardized interface for the fault management of the COTS HW.

Challenges are real——IT Grade vs. Carrier Grade

- ✓ “14 cloud outages in 7 months, who is next?” CIOList, 8/7/2012
- ✓ “Is The Cloud Really Ready For Business?” Forbes, 7/30/2012
- ✓ “Amazon Cloud Outage Causes Customer To Leave” InformationWeek, 7/6/2012

.....

- ✓ Research of 13 selected leading cloud service providers shows the Availability is **99.9%** and downtime cost them **70M USD** since 2007, which based on the cost benchmark of 2000. IWGCR, 6/17/2012
- ✓ Data center outage: overall average cost of **\$505,502 per incident**, more than **\$5,000 per minute**, 2/1/2011, Ponemon Institute
- ✓ Top ten cloud outages of 2013 accounted for a whopping revenue loss more than **\$31Million**
- ✓ The number of Cloud **outages rise quickly** with the growth of cloud services, CSA, 2013



Amazon's 7 Cloud Promises: Hype Vs. Reality

By Doug Hensollen 05/01/2013 Amazon says cloud computing is an indispensable enabler of seven important computing transformations. We hype-test the promises with a few reality checks.

< Previous 1 2 3 4 5 6 7 ... 18 Next >





99.9%?

99.999%?

Challenges are real——The way to Carrier Grade

Will high availability (five 9s) and customer experience could be kept as before when virtualization/cloud technologies are introduced?



All-IP drives the telecom industry In past 10 years and take years for IP's from IT to Telecom.

To meet with carrier grade, fault detection and Failover technologies should be improved for Telecom application:


- BFD、 enhance OAM, etc. : **faster fault detecting** ,less than 50ms (Vs. seconds before)
- E-VRRP , IGP FC, MPLS FRR etc.: **faster failover**, in hundreds microseconds (Vs. seconds before)

.....

History sometimes seems to repeat itself!

Challenges are real—New Change , New RAS risks (1)

- No SPOF enough? Redundancy enough?
- Elastic/distributed architecture seems beautiful but.....





Lessons from Telecom:

- Orange (France Telecom) outage, 2012.7
- O2 UK outage, 2012.7
- Verizon LTE outages, 2011~2012
- NTT DOCOMO outages, 2011~2012

.....


Challenges are real——New Change , New RAS risks (2)

- Load balancer
- Overload Control
- Behaviors of different Users, New Applications, New Smart Dives
- Traffic Models



Challenges are real——New Technologies , New RAS risks (3)

- Data Loss could be a more serious issue -----**Data Durability!**
- 0.07% of the volumes lost permanently during one Amazon outage last year.



99.9999999999% ?

Expressing P_3 as a sum of partial fractions

$$P_3(s) = \frac{A}{s} + \frac{B}{(s-r_1)} + \frac{C}{(s-r_2)} + \frac{D}{(s-r_3)}$$

We obtain

$$\begin{aligned} A &= 1 \\ B &= -\frac{6\lambda^3}{r_1(r_1-r_2)(r_1-r_3)} \\ C &= \frac{6\lambda^3}{r_2(r_2-r_1)(r_2-r_3)} \\ D &= -\frac{6\lambda^3}{r_3(r_3-r_1)(r_3-r_2)} \end{aligned}$$

Using Inverse Laplace transform

$$P_3(t) = A + Be^{r_1 t} + Ce^{r_2 t} + De^{r_3 t}$$

$$\text{Durability (data of 1 chunk)} = 1 - P_3(T \text{ is 1 year}) = 1 - Be^{r_1 T} - Ce^{r_2 T} - De^{r_3 T}$$



$$\begin{aligned} \text{Durability (data of Volume)} &= \text{Model 1 : } 1 - NT * \Pr(F_i) \\ &= \text{Model 2 : } 1 - \text{Min}(C_{NT}^3, \text{Partition_Number}) * \Pr(F_i) \end{aligned}$$

NT = total number of physical nodes

Our Design Philosophy for new RAS challenges

Design Philosophy for the new trends:

- **FC-DFR**-----Feature Centered DFR
- **SDA**----- Software Defined Availability
- **SAA**-----Soft-failure Awareed Availability



Thank you

www.huawei.com

Copyright©2014 Huawei Technologies Co., Ltd. All Rights Reserved.

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.